


KLLX

Pièce en croix pour KLL



Rayon: 300 mm

Exec. Std.

Sendzimir

Mat. Opt.

Galvanisé à chaud


Mat. Opt. PE

Revêtement en poudre

| | | | | | | |
|---|------|------|------|------|------|------|
| | 150 | 200 | 300 | 400 | 500 | 600 |
| A | 1021 | 1071 | 1171 | 1271 | 1371 | 1471 |

| HD | Référence | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Magasin | Unité |
|----|-------------------|---------|---------|------------|---------|--------|---|---------|-------|
| HD | KLLX60.150 | 60 | 141 | | | 3,131 | 1 | | STK |
| HD | KLLX60.200 | 60 | 191 | | | 3,232 | 1 | | STK |
| HD | KLLX60.300 | 60 | 291 | | | 4,421 | 1 | | STK |
| HD | KLLX60.400 | 60 | 391 | | | 4,875 | 1 | | STK |
| HD | KLLX60.450 | 60 | 443 | | | 5,102 | 1 | | STK |
| HD | KLLX60.500 | 60 | 491 | | | 5,329 | 1 | | STK |
| HD | KLLX60.600 | 60 | 591 | | | 5,782 | 1 | | STK |
| HD | KLLX85.150 | 85 | 145 | | | 3,525 | 1 | | STK |
| HD | KLLX85.200 | 85 | 195 | | | 4,032 | 1 | | STK |
| HD | KLLX85.300 | 85 | 295 | | | 5,221 | 1 | | STK |
| HD | KLLX85.400 | 85 | 395 | | | 5,675 | 1 | | STK |
| HD | KLLX85.450 | 85 | 445 | | | 5,902 | 1 | | STK |
| HD | KLLX85.500 | 85 | 495 | | | 6,129 | 1 | | STK |
| HD | KLLX85.600 | 85 | 595 | | | 6,582 | 1 | | STK |

A fixer avec:



Boulon et écrou autobloquant VM

Nombre minimal des boulons et des écrous VM6.10: 16 pièces.