

KLM100B45

Courbe horizontale à 45° pour KLM100



A fixer avec:



Boulon à collet
(DIN 603)
RBK

Ecoux elargi (DIN
6923)
RM

Rayon: 600 mm

Exec. Std.

Sendzimir

Mat. Opt.

Mat. Opt. PE

Revêtement en poudre

HD	Référence	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Magasin	Unité
-	KLM100B45.150	100	158			3,412	1		STK
-	KLM100B45.200	100	208			3,628	1		STK
-	KLM100B45.300	100	308			4,060	1		STK
-	KLM100B45.400	100	408			4,493	1		STK
-	KLM100B45.450	100	458			4,709	1		STK
-	KLM100B45.500	100	508			5,283	1		STK
-	KLM100B45.600	100	608			5,792	1		STK
-	KLM100B45.750	100	758			6,556	1		STK
-	KLM100B45.800	100	808			6,811	1		STK
-	KLM100B45.900	100	908			7,320	1		STK
-	KLM100B45.1000	100	1008			8,571	1		STK
-	ZMKLM100B45.150	100	158			3,412	1		STK
-	ZMKLM100B45.200	100	208			3,628	1		STK
-	ZMKLM100B45.300	100	308			4,060	1		STK
-	ZMKLM100B45.400	100	408			4,493	1		STK
-	ZMKLM100B45.450	100	458			4,709	1		STK
-	ZMKLM100B45.500	100	508			5,283	1		STK
-	ZMKLM100B45.600	100	608			5,792	1		STK
-	ZMKLM100B45.750	100	758			6,556	1		STK
-	ZMKLM100B45.800	100	808			6,811	1		STK
-	ZMKLM100B45.900	100	908			7,320	1		STK
-	ZMKLM100B45.1000	100	1008			8,571	1		STK

Nombre minimal des boulons et des écrous: 8 pièces.