


KLM100SB45

Courbe intérieure à 45° pour KLM100



A fixer avec:



Boulon à collet
(DIN 603)
RBK

Ecroû elargi (DIN
6923)
RM

Rayon: 600 mm

Exec. Std.

Sendzimir

Mat. Opt.

Mat. Opt. PE

Revêtement en poudre

HD	Référence	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Magasin	Unité
-	KLM100SB45.150	100	158			2,724	1		STK
-	KLM100SB45.200	100	208			2,840	1		STK
-	KLM100SB45.300	100	308			3,070	1		STK
-	KLM100SB45.400	100	408			3,300	1		STK
-	KLM100SB45.450	100	458			3,416	1		STK
-	KLM100SB45.500	100	508			3,531	1		STK
-	KLM100SB45.600	100	608			3,761	1		STK
-	KLM100SB45.750	100	758			4,107	1		STK
-	KLM100SB45.800	100	808			4,222	1		STK
-	KLM100SB45.900	100	908			4,453	1		STK
-	KLM100SB45.1000	100	1008			4,683	1		STK
-	ZMKLM100SB45.150	100	158			2,724	1		STK
-	ZMKLM100SB45.200	100	208			2,840	1		STK
-	ZMKLM100SB45.300	100	308			3,070	1		STK
-	ZMKLM100SB45.400	100	408			3,300	1		STK
-	ZMKLM100SB45.450	100	458			3,416	1		STK
-	ZMKLM100SB45.500	100	508			3,531	1		STK
-	ZMKLM100SB45.600	100	608			3,761	1		STK
-	ZMKLM100SB45.750	100	758			4,107	1		STK
-	ZMKLM100SB45.800	100	808			4,222	1		STK
-	ZMKLM100SB45.900	100	908			4,453	1		STK
-	ZMKLM100SB45.1000	100	1008			4,683	1		STK

Nombre minimal des boulons et des écrous: 8 pièces.