


KLM100VB45

Courbe extérieure à 45° pour KLM100



A fixer avec:



Boulon à collet
(DIN 603)
RBK

Ecroû elargi (DIN
6923)
RM

Rayon: 600 mm

Exec. Std.

Sendzimir

Mat. Opt.

Mat. Opt. PE

Revêtement en poudre

HD	Référence	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Magasin	Unité
-	KLM100VB45.150	100	158			2,637	1		STK
-	KLM100VB45.200	100	208			2,714	1		STK
-	KLM100VB45.300	100	308			2,868	1		STK
-	KLM100VB45.400	100	408			3,021	1		STK
-	KLM100VB45.450	100	458			3,098	1		STK
-	KLM100VB45.500	100	508			3,175	1		STK
-	KLM100VB45.600	100	608			3,329	1		STK
-	KLM100VB45.750	100	758			3,559	1		STK
-	KLM100VB45.800	100	808			3,636	1		STK
-	KLM100VB45.900	100	908			3,790	1		STK
-	KLM100VB45.1000	100	1008			3,943	1		STK
-	ZMKLM100VB45.150	100	158			2,637	1		STK
-	ZMKLM100VB45.200	100	208			2,714	1		STK
-	ZMKLM100VB45.300	100	308			2,868	1		STK
-	ZMKLM100VB45.400	100	408			3,021	1		STK
-	ZMKLM100VB45.450	100	458			3,098	1		STK
-	ZMKLM100VB45.500	100	508			3,175	1		STK
-	ZMKLM100VB45.600	100	608			3,329	1		STK
-	ZMKLM100VB45.750	100	758			3,559	1		STK
-	ZMKLM100VB45.800	100	808			3,636	1		STK
-	ZMKLM100VB45.900	100	908			3,790	1		STK
-	ZMKLM100VB45.1000	100	1008			3,943	1		STK

Nombre minimal des boulons et des écrous: 8 pièces.