

KLM125B45

Courbe horizontale pour KLM125



A fixer avec:



Boulon à collet
(DIN 603)
RBK

Ecoux elargi (DIN
6923)
RM

Rayon: 600 mm

Exec. Std.

Sendzimir

Mat. Opt.

Mat. Opt. PE

Revêtement en poudre

HD	Référence	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Magasin	Unité
-	KLM125B45.150	125	158			4,084	1		STK
-	KLM125B45.200	125	208			4,312	1		STK
-	KLM125B45.300	125	308			4,767	1		STK
-	KLM125B45.400	125	408			5,223	1		STK
-	KLM125B45.450	125	458			5,451	1		STK
-	KLM125B45.500	125	508			6,035	1		STK
-	KLM125B45.600	125	608			6,567	1		STK
-	KLM125B45.750	125	758			7,366	1		STK
-	KLM125B45.800	125	808			7,632	1		STK
-	KLM125B45.900	125	908			8,165	1		STK
-	KLM125B45.1000	125	1008			9,438	1		STK
-	ZMKLM125B45.150	125	158			4,084	1		STK
-	ZMKLM125B45.200	125	208			4,312	1		STK
-	ZMKLM125B45.300	125	308			4,767	1		STK
-	ZMKLM125B45.400	125	408			5,223	1		STK
-	ZMKLM125B45.450	125	458			5,451	1		STK
-	ZMKLM125B45.500	125	508			6,035	1		STK
-	ZMKLM125B45.600	125	608			6,567	1		STK
-	ZMKLM125B45.750	125	758			7,366	1		STK
-	ZMKLM125B45.800	125	808			7,632	1		STK
-	ZMKLM125B45.900	125	908			8,165	1		STK
-	ZMKLM125B45.1000	125	1008			9,438	1		STK

Nombre minimal des boulons et des écrous: 8 pièces.