


KLM125SB

Courbe intérieure pour KLM125



Rayon: 600 mm

Exec. Std.

Sendzimir

Mat. Opt.

Mat. Opt. PE

Revêtement en poudre

HD	Référence	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Magasin	Unité
-	KLM125SB150	125	158			5,061	1		STK
-	KLM125SB200	125	208			5,215	1		STK
-	KLM125SB300	125	308			5,522	1		STK
-	KLM125SB400	125	408			5,829	1		STK
-	KLM125SB450	125	458			5,983	1		STK
-	KLM125SB500	125	508			6,136	1		STK
-	KLM125SB600	125	608			6,443	1		STK
-	KLM125SB750	125	758			6,904	1		STK
-	KLM125SB800	125	808			7,058	1		STK
-	KLM125SB900	125	908			7,365	1		STK
-	KLM125SB1000	125	1008			7,672	1		STK
-	ZMKLM125SB150	125	158			5,061	1		STK
-	ZMKLM125SB200	125	208			5,215	1		STK
-	ZMKLM125SB300	125	308			5,522	1		STK
-	ZMKLM125SB400	125	408			5,829	1		STK
-	ZMKLM125SB450	125	458			5,983	1		STK
-	ZMKLM125SB500	125	508			6,136	1		STK
-	ZMKLM125SB600	125	608			6,443	1		STK
-	ZMKLM125SB750	125	758			6,904	1		STK
-	ZMKLM125SB800	125	808			7,058	1		STK
-	ZMKLM125SB900	125	908			7,365	1		STK
-	ZMKLM125SB1000	125	1008			7,672	1		STK

A fixer avec:



Boulon à collet
(DIN 603)
RBK

Ecroû elargi (DIN
6923)
RM

Nombre minimal des boulons et des écrous: 8 pièces.