

KLM125T

Pièce en T pour KLM125



| |
|--|
| Rayon: 600 mm |
| Exec. Std. Sendzimir |
| Mat. Opt. |
| Mat. Opt. PE Revêtement en poudre |

| | | | | | |
|---|------|------|------|------|------|
| | 200 | 300 | 400 | 500 | 600 |
| A | 1962 | 2062 | 2162 | 2262 | 2362 |

A fixer avec:



Boulon à collet
(DIN 603)
RBK

Ecoux elargi (DIN
6923)
RM

| HD | Référence | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Magasin | Unité |
|----|----------------------|---------|---------|------------|---------|--------|---|---------|-------|
| - | KLM125T150 | 125 | 158 | | | 13,043 | 1 | | STK |
| - | KLM125T200 | 125 | 208 | | | 13,601 | 1 | | STK |
| - | KLM125T300 | 125 | 308 | | | 14,716 | 1 | | STK |
| - | KLM125T400 | 125 | 408 | | | 15,808 | 1 | | STK |
| - | KLM125T450 | 125 | 458 | | | 16,360 | 1 | | STK |
| - | KLM125T500 | 125 | 508 | | | 16,912 | 1 | | STK |
| - | KLM125T600 | 125 | 608 | | | 19,316 | 1 | | STK |
| - | KLM125T750 | 125 | 758 | | | 21,156 | 1 | | STK |
| - | KLM125T800 | 125 | 808 | | | 21,769 | 1 | | STK |
| - | KLM125T900 | 125 | 908 | | | 23,655 | 1 | | STK |
| - | KLM125T1000 | 125 | 1008 | | | 24,958 | 1 | | STK |
| - | ZMKLM125T150 | 125 | 158 | | | 13,043 | 1 | | STK |
| - | ZMKLM125T200 | 125 | 208 | | | 13,601 | 1 | | STK |
| - | ZMKLM125T300 | 125 | 308 | | | 14,716 | 1 | | STK |
| - | ZMKLM125T400 | 125 | 408 | | | 15,808 | 1 | | STK |
| - | ZMKLM125T450 | 125 | 458 | | | 16,360 | 1 | | STK |
| - | ZMKLM125T500 | 125 | 508 | | | 16,912 | 1 | | STK |
| - | ZMKLM125T600 | 125 | 608 | | | 19,316 | 1 | | STK |
| - | ZMKLM125T750 | 125 | 758 | | | 21,156 | 1 | | STK |
| - | ZMKLM125T800 | 125 | 808 | | | 21,769 | 1 | | STK |
| - | ZMKLM125T900 | 125 | 908 | | | 23,655 | 1 | | STK |
| - | ZMKLM125T1000 | 125 | 1008 | | | 24,958 | 1 | | STK |

Nombre minimal des boulons et des écrous: 12 pièces.