


KLM125VB

Courbe extérieure pour KLM125



Rayon: 600 mm

Exec. Std.

Sendzimir

Mat. Opt.

Mat. Opt. PE

Revêtement en poudre

A fixer avec:



Ecrou elargi (DIN
6923)
RM

Boulon à collet
(DIN 603)
RBK

HD	Référence	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Magasin	Unité
-	KLM125VB150	125	158			4,974	1		STK
-	KLM125VB200	125	208			5,089	1		STK
-	KLM125VB300	125	308			5,320	1		STK
-	KLM125VB400	125	408			5,550	1		STK
-	KLM125VB450	125	458			5,666	1		STK
-	KLM125VB500	125	508			5,781	1		STK
-	KLM125VB600	125	608			6,011	1		STK
-	KLM125VB750	125	758			6,357	1		STK
-	KLM125VB800	125	808			6,472	1		STK
-	KLM125VB900	125	908			6,702	1		STK
-	KLM125VB1000	125	1008			6,933	1		STK
-	ZMKLM125VB150	125	158			4,974	1		STK
-	ZMKLM125VB200	125	208			5,089	1		STK
-	ZMKLM125VB300	125	308			5,320	1		STK
-	ZMKLM125VB400	125	408			5,550	1		STK
-	ZMKLM125VB450	125	458			5,666	1		STK
-	ZMKLM125VB500	125	508			5,781	1		STK
-	ZMKLM125VB600	125	608			6,011	1		STK
-	ZMKLM125VB750	125	758			6,357	1		STK
-	ZMKLM125VB800	125	808			6,472	1		STK
-	ZMKLM125VB900	125	908			6,702	1		STK
-	ZMKLM125VB1000	125	1008			6,933	1		STK

Nombre minimal des boulons et des écrous: 8 pièces.