


KLM125VB45

Courbe extérieure pour KLM125



A fixer avec:



Ecroû elargi (DIN
6923)
RM

Boulon à collet
(DIN 603)
RBK

Rayon: 600 mm

Exec. Std.

Sendzimir

Mat. Opt.

Mat. Opt. PE

Revêtement en poudre

HD	Référence	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Magasin	Unité
-	KLM125VB45.150	125	158			3,200	1		STK
-	KLM125VB45.200	125	208			3,276	1		STK
-	KLM125VB45.300	125	308			3,430	1		STK
-	KLM125VB45.400	125	408			3,584	1		STK
-	KLM125VB45.450	125	458			3,660	1		STK
-	KLM125VB45.500	125	508			3,737	1		STK
-	KLM125VB45.600	125	608			3,891	1		STK
-	KLM125VB45.750	125	758			4,121	1		STK
-	KLM125VB45.800	125	808			4,198	1		STK
-	KLM125VB45.900	125	908			4,352	1		STK
-	KLM125VB45.1000	125	1008			4,505	1		STK
-	ZMKLM125VB45.150	125	158			3,200	1		STK
-	ZMKLM125VB45.200	125	208			3,276	1		STK
-	ZMKLM125VB45.300	125	308			3,430	1		STK
-	ZMKLM125VB45.400	125	408			3,584	1		STK
-	ZMKLM125VB45.450	125	458			3,660	1		STK
-	ZMKLM125VB45.500	125	508			3,737	1		STK
-	ZMKLM125VB45.600	125	608			3,891	1		STK
-	ZMKLM125VB45.750	125	758			4,121	1		STK
-	ZMKLM125VB45.800	125	808			4,198	1		STK
-	ZMKLM125VB45.900	125	908			4,352	1		STK
-	ZMKLM125VB45.1000	125	1008			4,505	1		STK

Nombre minimal des boulons et des écrous: 8 pièces.