

# KLZSB

## Courbe intérieure pour KLZ



Rayon: 600 mm

Exec. Std.

Sendzimir

Mat. Opt.

Mat. Opt. PE

Revêtement en poudre

### A fixer avec:



Boulon à collet  
(DIN 603)  
RBK

Ecoux elargi (DIN  
6923)  
RM

HD	Référence	↕ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Magasin	Unité
-	<b>KLZSB200</b>	150	208			6,093	1		STK
-	<b>KLZSB300</b>	150	308			6,400	1		STK
-	<b>KLZSB400</b>	150	408			6,707	1		STK
-	<b>KLZSB500</b>	150	508			7,015	1		STK
-	<b>KLZSB600</b>	150	608			7,322	1		STK
-	<b>ZMKLZSB200</b>	150	208			6,093	1		STK
-	<b>ZMKLZSB300</b>	150	308			6,400	1		STK
-	<b>ZMKLZSB400</b>	150	408			6,707	1		STK
-	<b>ZMKLZSB500</b>	150	508			7,015	1		STK
-	<b>ZMKLZSB600</b>	150	608			7,322	1		STK

Nombre minimal des boulons et des écrous: 8 pièces.