

TFCL60S

TFCL met SIN



Te bevestigen met:



Koppelplaat
V35.200

Artikel	↑ mm	↔ mm	→ ← mm	↔ mm	kg/m	📦	Eenh.
TFCL60.100.200S12	60	100	2	3000	4,161	30	M
TFCL60.100.200S13	60	100	2	3000	4,161	30	M
TFCL60.150.200S12	60	150	2	3000	4,951	30	M
TFCL60.150.200S13	60	150	2	3000	4,951	30	M
TFCL60.150.200S23	60	150	2	3000	5,462	30	M
TFCL60.200.200S12	60	200	2	3000	5,761	30	M
TFCL60.200.200S13	60	200	2	3000	5,761	30	M
TFCL60.200.200S23	60	200	2	3000	6,272	30	M
TFCL60.250.200S12	60	250	2	3000	6,531	30	M
TFCL60.250.200S13	60	250	2	3000	6,531	30	M
TFCL60.250.200S23	60	250	2	3000	7,042	30	M
TFCL60.300.200S12	60	300	2	3000	7,361	30	M
TFCL60.300.200S13	60	300	2	3000	7,361	30	M
TFCL60.300.200S23	60	300	2	3000	7,872	30	M

S12: 1 scheidingsschot in het midden van de kabelgoot
 S13: 1 scheidingsschot op 1/3 van de rand van de kabelgoot
 S23: 2 scheidingsschotten op 1/3 van de rand van de kabelgoot