


KR

Kruisstuk

Ineenschuifbaar met de kabelbaan

Radius: 100 mm


Op aanvraag: Hoogte 35 mm - 85 mm - 110 mm



Te bevestigen met:



Zelfborgende
moer en bout
VM



Zelfborgende
moer en
kraagbout
VMK

Artikel	Afwerking	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Eenh.
ZMKR60.050	DF	60	50			0,922	1	STK
ZMKR60.075	DF	60	75			1,051	1	STK
ZMKR60.100	DF	60	100			1,187	1	STK
ZMKR60.150	DF	60	150			1,480	1	STK
ZMKR60.200	DF	60	200			1,801	1	STK
ZMKR60.300	DF	60	300			2,524	1	STK
ZMKR60.400	DF	60	400			3,357	1	STK
ZMKR60.500	DF	60	500			5,351	1	STK
ZMKR60.600	DF	60	600			6,704	1	STK
ZMKR85.100	DF	85	100	0,75		1,364	1	STK
ZMKR85.150	DF	85	150	0,75		1,657	1	STK
ZMKR85.200	DF	85	200	0,75		1,977	1	STK
ZMKR85.300	DF	85	300	0,75		2,700	1	STK
ZMKR85.400	DF	85	400	0,75		3,533	1	STK
ZMKR85.500	DF	85	500	0,75/0,9		5,527	1	STK
ZMKR85.600	DF	85	600	0,75/0,9		6,881	1	STK
ZMKR110.100	DF	110	100	0,75		1,545	1	STK
ZMKR110.150	DF	110	150	0,75		1,838	1	STK
ZMKR110.200	DF	110	200	0,75		2,158	1	STK
ZMKR110.300	DF	110	300	0,75		2,881	1	STK
ZMKR110.400	DF	110	400	0,75		3,714	1	STK
ZMKR110.500	DF	110	500	0,75/0,9		5,708	1	STK
ZMKR110.600	DF	110	600	0,75/0,9		7,062	1	STK

Minimum aantal bouten en moeren: 16 stuks.

Legende afwerking

- DF = Defender