

VH

Verstelbaar hoekstuk

Hoekstuk verstelbaar tussen 90° - 180°


Op aanvraag: Hoogte 35 mm - 85 mm - 110 mm (enkel in SZ en HD)



Te bevestigen met:



Zelfborgende
moer en bout
VM



Zelfborgende
moer en
kraagbout
VMK

| Artikel | Afwerking | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|--------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| ZMVH110.100 | DF | 110 | 100 | 0,9 | | 0,539 | 1 | STK |
| ZMVH110.150 | DF | 110 | 150 | 0,9 | | 0,629 | 1 | STK |
| ZMVH110.200 | DF | 110 | 200 | 0,9 | | 0,747 | 1 | STK |
| ZMVH110.300 | DF | 110 | 300 | 0,9 | | 1,189 | 1 | STK |
| ZMVH110.400 | DF | 110 | 400 | 0,9 | | 1,680 | 1 | STK |
| ZMVH110.500 | DF | 110 | 500 | 0,9 | | 2,344 | 1 | STK |
| ZMVH110.600 | DF | 110 | 600 | 0,9 | | 3,119 | 1 | STK |
| ZMVH85.100 | DF | 85 | 100 | 0,9 | | 0,433 | 1 | STK |
| ZMVH85.150 | DF | 85 | 150 | 0,9 | | 0,523 | 1 | STK |
| ZMVH85.200 | DF | 85 | 200 | 0,9 | | 0,641 | 1 | STK |
| ZMVH85.300 | DF | 85 | 300 | 0,9 | | 1,052 | 1 | STK |
| ZMVH85.400 | DF | 85 | 400 | 0,9 | | 1,528 | 1 | STK |
| ZMVH85.500 | DF | 85 | 500 | 0,9 | | 2,161 | 1 | STK |
| ZMVH85.600 | DF | 85 | 600 | 0,9 | | 2,905 | 1 | STK |
| ZMVH60.050 | DF | 60 | 50 | | | 0,264 | 1 | STK |
| ZMVH60.075 | DF | 60 | 75 | | | 0,292 | 1 | STK |
| ZMVH60.100 | DF | 60 | 100 | | | 0,326 | 1 | STK |
| ZMVH60.150 | DF | 60 | 150 | | | 0,417 | 1 | STK |
| ZMVH60.200 | DF | 60 | 200 | | | 0,534 | 1 | STK |
| ZMVH60.300 | DF | 60 | 300 | | | 0,915 | 1 | STK |
| ZMVH60.400 | DF | 60 | 400 | | | 1,376 | 1 | STK |
| ZMVH60.500 | DF | 60 | 500 | | | 1,978 | 1 | STK |
| ZMVH60.600 | DF | 60 | 600 | | | 2,692 | 1 | STK |

Minimum aantal bouten en moeren: 4 stuks.

Legende afwerking

- DF = Defender