

KLLB

Horizontale bocht voor KLL



Te bevestigen met:



Zelfborgende moer en bout
VM

Radius: 300 mm

| Artikel | Afwerking | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|----------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| ZMKLLB60.150 | DF | 60 | 150 | 1,25 | | 1,516 | 1 | STK |
| ZMKLLB60.200 | DF | 60 | 200 | 1,25 | | 1,695 | 1 | STK |
| ZMKLLB60.300 | DF | 60 | 300 | 1,25 | | 2,051 | 1 | STK |
| ZMKLLB60.400 | DF | 60 | 400 | 1,25 | | 3,067 | 1 | STK |
| ZMKLLB60.450 | DF | 60 | 450 | 1,25 | | 3,333 | 1 | STK |
| ZMKLLB60.500 | DF | 60 | 500 | 1,25 | | 3,598 | 1 | STK |
| ZMKLLB60.600 | DF | 60 | 600 | 1,25 | | 4,129 | 1 | STK |
| ZMKLLB60.750 | DF | 60 | 750 | 1,25 | | 4,926 | 1 | STK |
| ZMKLLB60.800 | DF | 60 | 800 | 1,25 | | 5,191 | 1 | STK |
| ZMKLLB60.900 | DF | 60 | 900 | 1,25 | | 5,722 | 1 | STK |
| ZMKLLB110.150 | DF | 110 | 150 | 1,25 | | 2,370 | 1 | STK |
| ZMKLLB110.200 | DF | 110 | 200 | 1,25 | | 2,586 | 1 | STK |
| ZMKLLB110.300 | DF | 110 | 300 | 1,25 | | 3,020 | 1 | STK |
| ZMKLLB110.400 | DF | 110 | 400 | 1,25 | | 4,112 | 1 | STK |
| ZMKLLB110.450 | DF | 110 | 450 | 1,25 | | 4,416 | 1 | STK |
| ZMKLLB110.500 | DF | 110 | 500 | 1,25 | | 4,720 | 1 | STK |
| ZMKLLB110.600 | DF | 110 | 600 | 1,25 | | 5,328 | 1 | STK |
| ZMKLLB110.750 | DF | 110 | 750 | 1,25 | | 6,239 | 1 | STK |
| ZMKLLB110.800 | DF | 110 | 800 | 1,25 | | 6,543 | 1 | STK |
| ZMKLLB110.900 | DF | 110 | 900 | 1,25 | | 7,151 | 1 | STK |
| KLLB60.150 | - | 60 | 141 | | | 1,659 | 1 | STK |
| KLLB60.200 | - | 60 | 191 | | | 1,898 | 1 | STK |
| KLLB60.300 | - | 60 | 291 | | | 2,375 | 1 | STK |
| KLLB60.400 | - | 60 | 391 | | | 2,852 | 1 | STK |
| KLLB60.450 | - | 60 | 443 | | | 3,091 | 1 | STK |
| KLLB60.500 | - | 60 | 491 | | | 3,329 | 1 | STK |
| KLLB60.600 | - | 60 | 591 | | | 3,806 | 1 | STK |
| KLLB60.750 | SZ | 60 | 750 | 1,25 | | 4,926 | 1 | STK |
| KLLB60.800 | SZ | 60 | 800 | 1,25 | | 5,191 | 1 | STK |
| KLLB60.900 | SZ | 60 | 900 | 1,25 | | 5,722 | 1 | STK |
| KLLB110.150 | - | 110 | 145 | | | 3,065 | 1 | STK |
| KLLB110.200 | - | 110 | 195 | | | 2,826 | 1 | STK |
| KLLB110.300 | - | 110 | 295 | | | 3,384 | 1 | STK |
| KLLB110.400 | - | 110 | 395 | | | 3,940 | 1 | STK |
| KLLB110.450 | - | 110 | 445 | | | 4,219 | 1 | STK |
| KLLB110.500 | - | 110 | 495 | | | 4,498 | 1 | STK |
| KLLB110.600 | - | 110 | 595 | | | 5,055 | 1 | STK |
| KLLB110.750 | - | 110 | 750 | | | 5,891 | 1 | STK |
| KLLB110.800 | SZ | 110 | 800 | 1,25 | | 6,543 | 1 | STK |
| KLLB110.900 | - | 110 | 900 | | | 6,727 | 1 | STK |

Minimum aantal bouten en moeren VM6.10: 8 stuks.

Legende afwerking

- DF = Defender
- SZ = Sendzimir

