


KLLT

T-stuk voor KLL



Radius: 300 mm

	150	200	300	400	500	600
A	1021	1071	1171	1271	1371	1471

Te bevestigen met:



Zelfborgende moer en bout
VM

Artikel	Afwerking	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Eenh.
KLLT60.150	-	60	141			2,229	1	STK
KLLT60.200	-	60	191			2,821	1	STK
KLLT60.300	-	60	291			3,447	1	STK
KLLT60.400	-	60	391			3,882	1	STK
KLLT60.450	-	60	443			4,099	1	STK
KLLT60.500	-	60	491			4,317	1	STK
KLLT60.600	-	60	591			4,753	1	STK
KLLT60.750	SZ	60	750	1,25		7,554	1	STK
KLLT60.800	SZ	60	800	1,25		7,896	1	STK
KLLT60.900	SZ	60	900	1,25		8,580	1	STK
KLLT110.150	-	110	145			3,635	1	STK
KLLT110.200	-	110	195			4,131	1	STK
KLLT110.300	-	110	295			4,806	1	STK
KLLT110.400	-	110	395			5,290	1	STK
KLLT110.450	-	110	445			5,533	1	STK
KLLT110.500	-	110	495			5,775	1	STK
KLLT110.600	-	110	595			6,260	1	STK
KLLT110.750	-	110	750			6,987	1	STK
KLLT110.800	SZ	110	800	1,25		9,478	1	STK
KLLT110.900	-	110	900			7,714	1	STK
ZMKLLT60.150	DF	60	150	1,25		3,229	1	STK
ZMKLLT60.200	DF	60	200	1,25		3,483	1	STK
ZMKLLT60.300	DF	60	300	1,25		4,154	1	STK
ZMKLLT60.400	DF	60	400	1,25		4,721	1	STK
ZMKLLT60.450	DF	60	450	1,25		5,005	1	STK
ZMKLLT60.500	DF	60	500	1,25		5,566	1	STK
ZMKLLT60.600	DF	60	600	1,25		6,193	1	STK
ZMKLLT60.750	DF	60	750	1,25		7,554	1	STK
ZMKLLT60.800	DF	60	800	1,25		7,896	1	STK
ZMKLLT60.900	DF	60	900	1,25		8,580	1	STK
ZMKLLT110.150	DF	110	150	1,25		4,493	1	STK
ZMKLLT110.200	DF	110	200	1,25		4,772	1	STK
ZMKLLT110.300	DF	110	300	1,25		5,491	1	STK
ZMKLLT110.400	DF	110	400	1,25		6,107	1	STK
ZMKLLT110.450	DF	110	450	1,25		6,416	1	STK
ZMKLLT110.500	DF	110	500	1,25		7,001	1	STK
ZMKLLT110.600	DF	110	600	1,25		7,677	1	STK
ZMKLLT110.750	DF	110	750	1,25		9,111	1	STK
ZMKLLT110.800	DF	110	800	1,25		9,478	1	STK
ZMKLLT110.900	DF	110	900	1,25		10,210	1	STK

Minimum aantal bouten en moeren VM6.10: 12 stuks.



Legende afwerking

- SZ = Sendzimir
- DF = Defender