

KLM100B45

Horizontale bocht 45° voor KLM100



Te bevestigen met:



Zelfborgende
kraagbout (DIN
603)
RBK



Zelfborgende
flensmoer (DIN
6923)
RM

Radius: 600 mm

Artikel	Afwerking	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Eenh.
KLM100B45.150	SZ	100	158			3,412	1	STK
KLM100B45.200	SZ	100	208			3,628	1	STK
KLM100B45.300	SZ	100	308			4,060	1	STK
KLM100B45.400	SZ	100	408			4,493	1	STK
KLM100B45.450	SZ	100	458			4,709	1	STK
KLM100B45.500	SZ	100	508			5,283	1	STK
KLM100B45.600	SZ	100	608			5,792	1	STK
KLM100B45.750	SZ	100	758			6,556	1	STK
KLM100B45.800	SZ	100	808			6,811	1	STK
KLM100B45.900	SZ	100	908			7,320	1	STK
KLM100B45.1000	SZ	100	1008			8,571	1	STK
ZMKLM100B45.150	DF	100	158			3,412	1	STK
ZMKLM100B45.200	DF	100	208			3,628	1	STK
ZMKLM100B45.300	DF	100	308			4,060	1	STK
ZMKLM100B45.400	DF	100	408			4,493	1	STK
ZMKLM100B45.450	DF	100	458			4,709	1	STK
ZMKLM100B45.500	DF	100	508			5,283	1	STK
ZMKLM100B45.600	DF	100	608			5,792	1	STK
ZMKLM100B45.750	DF	100	758			6,556	1	STK
ZMKLM100B45.800	DF	100	808			6,811	1	STK
ZMKLM100B45.900	DF	100	908			7,320	1	STK
ZMKLM100B45.1000	DF	100	1008			8,571	1	STK

Minimum aantal bouten en moeren: 8 stuks.

Legende afwerking

- SZ = Sendzimir
- DF = Defender