

DKLMZWVB45

Deksel voor ladder valbocht 45°



Te bevestigen met:



Dekselklem
ZMDKIG

Radius: 600 mm

| Artikel | Afwerking | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|---------------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| DKLM125VB45.150 | SZ | 15 | 156 | 0,9 | | 0,835 | 1 | STK |
| DKLM125VB45.200 | SZ | 15 | 206 | 0,9 | | 1,117 | 1 | STK |
| DKLM125VB45.300 | SZ | 15 | 306 | 0,9 | | 1,608 | 1 | STK |
| DKLM125VB45.400 | SZ | 15 | 406 | 0,9 | | 2,234 | 1 | STK |
| DKLM125VB45.450 | SZ | 15 | 456 | 0,9 | | 2,525 | 1 | STK |
| DKLM125VB45.500 | SZ | 15 | 506 | 0,9 | | 2,806 | 1 | STK |
| DKLM125VB45.600 | SZ | 15 | 606 | 0,9 | | 3,370 | 1 | STK |
| DKLM125VB45.750 | SZ | 15 | 756 | 1,25 | | 5,852 | 1 | STK |
| DKLM125VB45.800 | SZ | 15 | 806 | 1,25 | | 6,243 | 1 | STK |
| DKLM125VB45.900 | SZ | 15 | 906 | 1,25 | | 7,025 | 1 | STK |
| DKLM125VB45.1000 | SZ | 15 | 1006 | 1,25 | | 7,887 | 1 | STK |
| ZMDKLM125VB45.150 | DF | 15 | 156 | 0,9 | | 0,835 | 1 | STK |
| ZMDKLM125VB45.200 | DF | 15 | 206 | 0,9 | | 1,117 | 1 | STK |
| ZMDKLM125VB45.300 | DF | 15 | 306 | 0,9 | | 1,608 | 1 | STK |
| ZMDKLM125VB45.400 | DF | 15 | 406 | 0,9 | | 2,234 | 1 | STK |
| ZMDKLM125VB45.450 | DF | 15 | 456 | 0,9 | | 2,525 | 1 | STK |
| ZMDKLM125VB45.500 | DF | 15 | 506 | 0,9 | | 2,806 | 1 | STK |
| ZMDKLM125VB45.600 | DF | 15 | 606 | 0,9 | | 3,370 | 1 | STK |
| ZMDKLM125VB45.750 | DF | 15 | 756 | 1,25 | | 5,852 | 1 | STK |
| ZMDKLM125VB45.800 | DF | 15 | 806 | 1,25 | | 6,243 | 1 | STK |
| ZMDKLM125VB45.900 | DF | 15 | 906 | 1,25 | | 7,025 | 1 | STK |
| ZMDKLM125VB45.1000 | DF | 15 | 1006 | 1,25 | | 7,887 | 1 | STK |

Deksel voor standaard ladderaccessoires Deksel kan worden gebruikt voor ladders KLM100-KLM125-KLW-KLZ

Legende afwerking

- SZ = Sendzimir
- DF = Defender