

KLM125B

Horizontale bocht voor KLM125



Te bevestigen met:



Zelfborgende
kraagbout (DIN
603)
RBK

Zelfborgende
flensmoer (DIN
6923)
RM

Radius: 600 mm

| Artikel | Afwerking | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|----------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| KLM125B150 | SZ | 125 | 158 | | | 6,297 | 1 | STK |
| KLM125B200 | SZ | 125 | 208 | | | 6,714 | 1 | STK |
| KLM125B300 | SZ | 125 | 308 | | | 7,548 | 1 | STK |
| KLM125B400 | SZ | 125 | 408 | | | 8,383 | 1 | STK |
| KLM125B450 | SZ | 125 | 458 | | | 8,800 | 1 | STK |
| KLM125B500 | SZ | 125 | 508 | | | 9,217 | 1 | STK |
| KLM125B600 | SZ | 125 | 608 | | | 10,052 | 1 | STK |
| KLM125B750 | SZ | 125 | 758 | | | 12,400 | 1 | STK |
| KLM125B800 | SZ | 125 | 808 | | | 12,894 | 1 | STK |
| KLM125B900 | SZ | 125 | 908 | | | 13,883 | 1 | STK |
| KLM125B1000 | SZ | 125 | 1008 | | | 17,871 | 1 | STK |
| ZMKLM125B150 | DF | 125 | 158 | | | 6,297 | 1 | STK |
| ZMKLM125B200 | DF | 125 | 208 | | | 6,714 | 1 | STK |
| ZMKLM125B300 | DF | 125 | 308 | | | 7,548 | 1 | STK |
| ZMKLM125B400 | DF | 125 | 408 | | | 8,383 | 1 | STK |
| ZMKLM125B450 | DF | 125 | 458 | | | 8,800 | 1 | STK |
| ZMKLM125B500 | DF | 125 | 508 | | | 9,217 | 1 | STK |
| ZMKLM125B600 | DF | 125 | 608 | | | 10,052 | 1 | STK |
| ZMKLM125B750 | DF | 125 | 758 | | | 12,400 | 1 | STK |
| ZMKLM125B800 | DF | 125 | 808 | | | 12,894 | 1 | STK |
| ZMKLM125B900 | DF | 125 | 908 | | | 13,883 | 1 | STK |
| ZMKLM125B1000 | DF | 125 | 1008 | | | 17,871 | 1 | STK |

Minimum aantal bouten en moeren: 8 stuks.

Legende afwerking

- SZ = Sendzimir
- DF = Defender