


KLM125T

T-stuk voor KLM125



Te bevestigen met:



Zelfborgende
kraagbout (DIN
603)
RBK

Zelfborgende
flensmoer (DIN
6923)
RM

Radius: 600 mm

	200	300	400	500	600
A	1962	2062	2162	2262	2362

Artikel	Afwerking	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Eenh.
KLM125T150	SZ	125	158			13,043	1	STK
KLM125T200	SZ	125	208			13,601	1	STK
KLM125T300	SZ	125	308			14,716	1	STK
KLM125T400	SZ	125	408			15,808	1	STK
KLM125T450	SZ	125	458			16,360	1	STK
KLM125T500	SZ	125	508			16,912	1	STK
KLM125T600	SZ	125	608			19,316	1	STK
KLM125T750	SZ	125	758			21,156	1	STK
KLM125T800	SZ	125	808			21,769	1	STK
KLM125T900	SZ	125	908			23,655	1	STK
KLM125T1000	SZ	125	1008			24,958	1	STK
ZMKLM125T150	DF	125	158			13,043	1	STK
ZMKLM125T200	DF	125	208			13,601	1	STK
ZMKLM125T300	DF	125	308			14,716	1	STK
ZMKLM125T400	DF	125	408			15,808	1	STK
ZMKLM125T450	DF	125	458			16,360	1	STK
ZMKLM125T500	DF	125	508			16,912	1	STK
ZMKLM125T600	DF	125	608			19,316	1	STK
ZMKLM125T750	DF	125	758			21,156	1	STK
ZMKLM125T800	DF	125	808			21,769	1	STK
ZMKLM125T900	DF	125	908			23,655	1	STK
ZMKLM125T1000	DF	125	1008			24,958	1	STK

Minimum aantal bouten en moeren: 12 stuks.

Legende afwerking

- SZ = Sendzimir
- DF = Defender