


KLWVB Valbocht voor KLW



Te bevestigen met:



Zelfborgende
flensmoer (DIN
6923)
RM

Zelfborgende
kraagbout (DIN
603)
RBK

Radius: 600 mm

| Artikel | Afwerking | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|-------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| KLWVB200 | SZ | 200 | 208 | | | 7,795 | 1 | STK |
| KLWVB300 | SZ | 200 | 308 | | | 8,026 | 1 | STK |
| KLWVB400 | SZ | 200 | 408 | | | 8,256 | 1 | STK |
| KLWVB500 | SZ | 200 | 508 | | | 8,487 | 1 | STK |
| KLWVB600 | SZ | 200 | 608 | | | 8,717 | 1 | STK |
| ZMKLWVB200 | DF | 200 | 208 | | | 7,795 | 1 | STK |
| ZMKLWVB300 | DF | 200 | 308 | | | 8,026 | 1 | STK |
| ZMKLWVB400 | DF | 200 | 408 | | | 8,256 | 1 | STK |
| ZMKLWVB500 | DF | 200 | 508 | | | 8,487 | 1 | STK |
| ZMKLWVB600 | DF | 200 | 608 | | | 8,717 | 1 | STK |

Minimum aantal bouten en moeren: 8 stuks.

Legende afwerking

- SZ = Sendzimir
- DF = Defender