

DKLMZWVB45

Deksel voor ladder valbocht 45°



Te bevestigen met:



Dekselklem
ZMDKIG

Radius: 600 mm

| Artikel | Afwerking | ↕ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|------------------------|-----------|---------|---------|------------|---------|--------|---|-------|
| DKLZVB45.150 | SZ | 15 | 156 | 0,9 | | 0,857 | 1 | STK |
| DKLZVB45.200 | SZ | 15 | 206 | 0,9 | | 1,146 | 1 | STK |
| DKLZVB45.300 | SZ | 15 | 306 | 0,9 | | 1,723 | 1 | STK |
| DKLZVB45.400 | SZ | 15 | 406 | 0,9 | | 2,300 | 1 | STK |
| DKLZVB45.450 | SZ | 15 | 456 | 0,9 | | 2,589 | 1 | STK |
| DKLZVB45.500 | SZ | 15 | 506 | 0,9 | | 2,878 | 1 | STK |
| DKLZVB45.600 | SZ | 15 | 606 | 0,9 | | 3,455 | 1 | STK |
| DKLZVB45.750 | SZ | 15 | 756 | 1,25 | | 6,000 | 1 | STK |
| DKLZVB45.800 | SZ | 15 | 806 | 1,25 | | 6,400 | 1 | STK |
| DKLZVB45.900 | SZ | 15 | 906 | 1,25 | | 7,202 | 1 | STK |
| DKLZVB45.1000 | SZ | 15 | 1006 | 1,25 | | 8,083 | 1 | STK |
| ZMDKLZVB45.150 | DF | 15 | 156 | 0,9 | | 0,857 | 1 | STK |
| ZMDKLZVB45.200 | DF | 15 | 206 | 0,9 | | 1,146 | 1 | STK |
| ZMDKLZVB45.300 | DF | 15 | 306 | 0,9 | | 1,723 | 1 | STK |
| ZMDKLZVB45.400 | DF | 15 | 406 | 0,9 | | 2,300 | 1 | STK |
| ZMDKLZVB45.450 | DF | 15 | 456 | 0,9 | | 2,589 | 1 | STK |
| ZMDKLZVB45.500 | DF | 15 | 506 | 0,9 | | 2,878 | 1 | STK |
| ZMDKLZVB45.600 | DF | 15 | 606 | 0,9 | | 3,455 | 1 | STK |
| ZMDKLZVB45.750 | DF | 15 | 756 | 1,25 | | 6,000 | 1 | STK |
| ZMDKLZVB45.800 | DF | 15 | 806 | 1,25 | | 6,400 | 1 | STK |
| ZMDKLZVB45.900 | DF | 15 | 906 | 1,25 | | 7,202 | 1 | STK |
| ZMDKLZVB45.1000 | DF | 15 | 1006 | 1,25 | | 8,083 | 1 | STK |

Deksel voor standaard ladderaccessoires Deksel kan worden gebruikt voor ladders KLM100-KLM125-KLW-KLZ

Legende afwerking

- SZ = Sendzimir
- DF = Defender