


# HDHSLECL

## Enkele hangsteun clipsbaar



Hangsteunprofiel: HDMP41.21  
Gelaste kopplaat: 135x135 mm

Max. Belasting: 1000 daN  
Dikte kopplaat: 4 mm

Stand. Uitv.

Hot-Dip

Mat. Opt. PE

Duplex

HD Artikel	↕ mm	↔ mm	→  ← mm	↔↔ mm	kg/stk	📦	Stock	Eenh.
- <b>HDHSLECL200</b>	210	21			0,740	25	X	STK
- <b>HDHSLECL300</b>	300	21			0,850	1	X	STK
- <b>HDHSLECL400</b>	420	21			1,010	1	X	STK
- <b>HDHSLECL500</b>	510	21			1,130	1	X	STK
- <b>HDHSLECL600</b>	600	21			1,230	1	X	STK
- <b>HDHSLECL800</b>	810	21			1,450	1	X	STK
- <b>HDHSLECL1000</b>	1020	21			1,750	1	X	STK
- <b>HDHSLECL1200</b>	1200	21			1,950	1	X	STK

Voor enkel- of dubbelzijdige ophanging van de console KCL en enkelzijdige ophanging van de consoles WKS, WKML en HDWK dmv glijmoer PNP10 en drukbout B10.20.

Beschermddop in gele PVC: DOP41.21.

