


# HSLE3

## Enkele hangsteun, perfo 3 zijdes



Hangsteunprofiel: MP3.41.41  
Gelaste kopplaat: 135x135 mm

Max. Belasting: 1800 daN  
Dikte kopplaat: 5 mm

Stand. Uitv. Elektrolytisch verzinkt  
Mat. Opt. Hot-Dip

HD Artikel	mm	mm	mm	mm	kg/stk	Stock	Eenh.
HD <b>HSLE3.300</b>	300	41			0,970	X	STK
HD <b>HSLE3.400</b>	400	41			1,090	X	STK
HD <b>HSLE3.500</b>	500	41			1,220	X	STK
HD <b>HSLE3.600</b>	600	41			1,340	X	STK
HD <b>HSLE3.700</b>	700	41			1,470	X	STK
HD <b>HSLE3.800</b>	800	41			1,590	X	STK
HD <b>HSLE3.900</b>	900	41			1,720	X	STK
HD <b>HSLE3.1000</b>	1000	41			1,840	X	STK
HD <b>HSLE3.1200</b>	1200	41			2,090	X	STK
HD <b>HSLE3.1500</b>	1500	41			2,470	X	STK

Langs 4 zijden te monteren: 3 zijden via perforaties d.m.v. WKCL console, 1 zijde waarbij je met glijmoer PNP10 en drukbout B10.30 kunt verankeren. Beschermddop in gele PVC: DOP41.41.

