

LOMEGACLU150

Wandbeugel universeel



Stand. Uitv.	Sendzimir
Mat. Opt.	Hot-Dip
Mat. Opt. PE	Poedercoating

	Max. belasting (in daN)
LOMEGACLU150.100	110
LOMEGACLU150.150	100
LOMEGACLU150.200	90
LOMEGACLU150.250	80
LOMEGACLU150.300	70
LOMEGACLU150.400	50
LOMEGACLU150.500	40
LOMEGACLU150.600	30

HD Artikel	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Eenh.
HD LOMEGACLU150.100	145	155			0,300	12	X	STK
HD LOMEGACLU150.150	145	185			0,320	12	X	STK
HD LOMEGACLU150.200	145	235			0,340	12	X	STK
HD LOMEGACLU150.250	145	285			0,450	12	X	STK
HD LOMEGACLU150.300	145	335			0,490	12	X	STK
HD LOMEGACLU150.400	145	435			0,540	6	X	STK
HD LOMEGACLU150.500	145	535			0,710	6	X	STK
HD LOMEGACLU150.600	145	635			0,770	6	X	STK

Te bestellen per volle verpakking.
 Bevestiging van een kabelbaan door VM6.20.
 Bij montage gebruik maken van de VOMEGA om het samendrukken van het profiel te verhinderen.
 Max. Belasting (daN): Gelijkmatig verdeeld over de volledige breedte.

Niet te gebruiken voor VFUL30.065, VFUL35.150, VFU35.150, VFUL 60.050.