

# P1000T

## Montageprofiel



Artikel	Afwerking	↕ mm	↔ mm	→  ← mm	↔ mm	kg/m	📦	Eenh.
<b>P1000TP</b>	PO	41	41	2,5	6000	2,605	6	M
<b>P1000T</b>	PG	41	41	2,5	6000	2,647	6	M
<b>P1000TH</b>	DF	41	41	2,5	6000	2,647	6	M
<b>P1000TDF</b>	DF	41	41	2,5	6000	2,647	6	M
<b>P1000TPX3</b>	PO	41	41	2,5	3000	2,605	3	M
<b>P1000TX3</b>	PG	41	41	2,5	3000	2,730	3	M
<b>P1000THX3</b>	ZP	41	41	2,5	3000	2,730	3	M
<b>P1000TX3DF</b>	DF	41	41	2,5	3000	2,647	3	M
<b>P1000TX2000</b>	PG	41	41	2,5	3000	2,462	2	M
<b>P1000THX2000</b>	HG	41	41	2,50	2000	2,730	2	M

T = 28x14mm

Afkorting:

- PO = Onbehandeld
- ZP = Verzinkt
- HG = Hot-dip Gegalvaniseerd
- DF = Defender

### Legende afwerking

- PO = Onbehandeld
- PG = Voorverzinkt
- DF = Defender
- ZP = Elektrolytisch verzinkt
- HG = Thermisch verzinkt