


I6KLM100VB

Valbocht voor I6KLM100



Radius: 600 mm

| Artikel | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|-----------------------|---------|---------|------------|---------|--------|---|-------|
| I6KLM100VB150 | 100 | 150 | | | 4,228 | 1 | STK |
| I6KLM100VB200 | 100 | 208 | | | 4,346 | 1 | STK |
| I6KLM100VB300 | 100 | 308 | | | 4,582 | 1 | STK |
| I6KLM100VB400 | 100 | 408 | | | 4,819 | 1 | STK |
| I6KLM100VB450 | 100 | 450 | | | 4,937 | 1 | STK |
| I6KLM100VB500 | 100 | 508 | | | 5,055 | 1 | STK |
| I6KLM100VB600 | 100 | 608 | | | 5,292 | 1 | STK |
| I6KLM100VB750 | 100 | 750 | | | 5,645 | 1 | STK |
| I6KLM100VB800 | 100 | 800 | | | 5,764 | 1 | STK |
| I6KLM100VB900 | 100 | 900 | | | 6,000 | 1 | STK |
| I6KLM100VB1000 | 100 | 1000 | | | 6,236 | 1 | STK |

Te bevestigen met:



Sluitring (DIN 125-1 A)
I6RO

Moer (DIN 934)
I6M



Zelfborgende kraagbout
I6RBK

Minimum aantal bouten en moeren: 8 stuks.

Gebeitst en gepassiveerd.