

I6KLM100VB45

Valbocht 45° voor I6KLM100



Radius: 600 mm

| Artikel | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|--------------------------|---------|---------|------------|---------|--------|---|-------|
| I6KLM100VB45.150 | 100 | 150 | | | 2,704 | 1 | STK |
| I6KLM100VB45.200 | 100 | 200 | | | 2,783 | 1 | STK |
| I6KLM100VB45.300 | 100 | 300 | | | 2,941 | 1 | STK |
| I6KLM100VB45.400 | 100 | 400 | | | 3,097 | 1 | STK |
| I6KLM100VB45.450 | 100 | 450 | | | 3,176 | 1 | STK |
| I6KLM100VB45.500 | 100 | 500 | | | 3,255 | 1 | STK |
| I6KLM100VB45.600 | 100 | 600 | | | 3,413 | 1 | STK |
| I6KLM100VB45.750 | 100 | 750 | | | 3,649 | 1 | STK |
| I6KLM100VB45.800 | 100 | 800 | | | 3,728 | 1 | STK |
| I6KLM100VB45.900 | 100 | 900 | | | 3,886 | 1 | STK |
| I6KLM100VB45.1000 | 100 | 1000 | | | 4,043 | 1 | STK |

Te bevestigen met:



Zelfborgende
kraagbout (DIN
603)
RBK

Zelfborgende
flensmoer (DIN
6923)
RM

Minimum aantal bouten en moeren: 8 stuks.