

I6KLM125B

Horizontale bocht voor I6KLM125



Te bevestigen met:



Zelfborgende
kraagbout
I6RBK

Moer (DIN 934)
I6M



Sluitring (DIN
125-1 A)
I6RO

Radius: 600 mm

| Artikel | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/stk | 📦 | Eenh. |
|----------------------|---------|---------|------------|---------|--------|---|-------|
| I6KLM125B150 | 125 | 150 | | | 6,456 | 1 | STK |
| I6KLM125B200 | 125 | 208 | | | 6,884 | 1 | STK |
| I6KLM125B300 | 125 | 308 | | | 7,739 | 1 | STK |
| I6KLM125B400 | 125 | 408 | | | 8,595 | 1 | STK |
| I6KLM125B450 | 125 | 450 | | | 9,023 | 1 | STK |
| I6KLM125B500 | 125 | 508 | | | 9,450 | 1 | STK |
| I6KLM125B600 | 125 | 608 | | | 10,306 | 1 | STK |
| I6KLM125B750 | 125 | 750 | | | 12,714 | 1 | STK |
| I6KLM125B800 | 125 | 800 | | | 13,220 | 1 | STK |
| I6KLM125B900 | 125 | 900 | | | 14,234 | 1 | STK |
| I6KLM125B1000 | 125 | 1000 | | | 18,323 | 1 | STK |

Minimum aantal bouten en moeren: 8 stuks.

Gebeitst en gepassiveerd.