


# I6KLM125VB

## Valbocht voor I6KLM125



Radius: 600 mm

| Artikel               | ↑<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦 | Eenh. |
|-----------------------|---------|---------|------------|---------|--------|---|-------|
| <b>I6KLM125VB150</b>  | 125     | 150     |            |         | 5,100  | 1 | STK   |
| <b>I6KLM125VB200</b>  | 125     | 208     |            |         | 5,218  | 1 | STK   |
| <b>I6KLM125VB300</b>  | 125     | 308     |            |         | 5,455  | 1 | STK   |
| <b>I6KLM125VB400</b>  | 125     | 408     |            |         | 5,691  | 1 | STK   |
| <b>I6KLM125VB450</b>  | 125     | 450     |            |         | 5,809  | 1 | STK   |
| <b>I6KLM125VB500</b>  | 125     | 508     |            |         | 5,927  | 1 | STK   |
| <b>I6KLM125VB600</b>  | 125     | 608     |            |         | 6,163  | 1 | STK   |
| <b>I6KLM125VB750</b>  | 125     | 750     |            |         | 6,518  | 1 | STK   |
| <b>I6KLM125VB800</b>  | 125     | 800     |            |         | 6,636  | 1 | STK   |
| <b>I6KLM125VB900</b>  | 125     | 900     |            |         | 6,872  | 1 | STK   |
| <b>I6KLM125VB1000</b> | 125     | 1000    |            |         | 7,109  | 1 | STK   |

### Te bevestigen met:



Zelfborgende  
kraagbout  
I6RBK

Moer (DIN 934)  
I6M

Minimum aantal bouten en moeren: 8 stuks.

Gebeitst en gepassiveerd.



Sluitring (DIN  
125-1 A)  
I6RO