

VGLI28

Lichte vloergoot ineenschuifbaar



Met 2 of 3 compartimenten.

Dikte deksel: 1,00 mm

Dikte bodemplaat: 1,00 mm

| Artikel | ↑ mm | ↔ mm | → ← mm | ↔ mm | kg/m | 📦 | Eenh. |
|-----------------------|---------|---------|------------|---------|-------|-----|-------|
| VGLI28.170S1 | 28 | 170 | | 3000 | 3,976 | 150 | M |
| VGLI28.170S2 | 28 | 170 | | 3000 | 4,475 | 150 | M |
| VGLI28.250S1 | 28 | 250 | | 3000 | 5,232 | 150 | M |
| VGLI28.250S1.2 | 28 | 250 | | 2000 | 5,232 | 300 | M |
| VGLI28.250S2 | 28 | 250 | | 3000 | 5,935 | 150 | M |
| VGLI28.250S2.2 | 28 | 250 | | 2000 | 5,935 | 300 | M |
| VGLI28.350S1 | 28 | 350 | | 3000 | 6,802 | 150 | M |
| VGLI28.350S1.2 | 28 | 350 | | 2000 | 6,802 | 300 | M |
| VGLI28.350S2 | 28 | 350 | | 3000 | 7,772 | 150 | M |
| VGLI28.350S2.2 | 28 | 350 | | 2000 | 7,772 | 300 | M |

Getest volgens EN 50085-2-2.

In totaal 16 voorgeboorde bevestigingspunten beschikbaar per lengte.

Geen supplementaire stukken nodig voor equipotentiaal verbinding.

Het product is gepatenteerd.