


KR

Kruisstuk



Ineenschuifbaar met de kabelbaan

Radius: 100 mm

Op aanvraag: Hoogte 35 mm - 85 mm - 110 mm

Stand. Uitv.

Sendzimir

Mat. Opt.

Mat. Opt. PE


Poedercoating

HD	Artikel	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Eenh.
-	KR60.050	60	50			1,180	1	X	STK
-	KR60.075	60	75			1,560	1	X	STK
-	KR60.100	60	100			1,480	1	X	STK
-	KR60.150	60	150			2,080	1	X	STK
-	KR60.200	60	200			2,380	1	X	STK
-	KR60.300	60	300			3,520	1	X	STK
-	KR60.400	60	400			4,610	1	X	STK
-	KR60.500	60	500			5,320	1	X	STK
-	KR60.600	60	600			6,160	1	X	STK
-	ZMKR60.050	60	50			1,595	1	X	STK
-	ZMKR60.075	60	75			1,815	1	X	STK
-	ZMKR60.100	60	100			1,925	1	X	STK
-	ZMKR60.150	60	150			2,31	1	X	STK
-	ZMKR60.200	60	200			2,53	1	X	STK
-	ZMKR60.300	60	300			4,18	1	X	STK
-	ZMKR60.400	60	400			5,17	1	X	STK
-	ZMKR60.500	60	500			8,03	1	X	STK
-	ZMKR60.600	60	600			9,68	1	X	STK

Te bevestigen met:



Zelfborgende
moer en bout
VM



Zelfborgende
moer en
kraagbout
VMK

Minimum aantal bouten en moeren: 16 stuks.