


# VB90

## Valbocht 90°



Ineenschuifbaar met de kabelbaan

Radius: 100 mm

Op aanvraag: Hoogte 35 mm - 85 mm - 110 mm

Stand. Uitv.

Sendzimir

Mat. Opt.

Mat. Opt. PE


Poedercoating

HD	Artikel	↕ mm	↔ mm	→  ← mm	↔ mm	kg/stk	📦	Stock	Eenh.
-	<b>VB90.60.050</b>	60	50			0,550	1	X	STK
-	<b>VB90.60.075</b>	60	75			0,630	1	X	STK
-	<b>VB90.60.100</b>	60	100			0,650	1	X	STK
-	<b>VB90.60.150</b>	60	150			0,780	1	X	STK
-	<b>VB90.60.200</b>	60	200			0,850	1	X	STK
-	<b>VB90.60.300</b>	60	300			1,080	1	X	STK
-	<b>VB90.60.400</b>	60	400			1,330	1	X	STK
-	<b>VB90.60.500</b>	60	500			1,430	1	X	STK
-	<b>VB90.60.600</b>	60	600			1,600	1	X	STK
-	<b>ZMVB90.60.050</b>	60	50			0,55	1		STK
-	<b>ZMVB90.60.075</b>	60	75			0,63	1		STK
-	<b>ZMVB90.60.100</b>	60	100			0,65	1		STK
-	<b>ZMVB90.60.150</b>	60	150			0,78	1		STK
-	<b>ZMVB90.60.200</b>	60	200			0,85	1		STK
-	<b>ZMVB90.60.300</b>	60	300			1,08	1		STK
-	<b>ZMVB90.60.400</b>	60	400			1,33	1		STK
-	<b>ZMVB90.60.500</b>	60	500			1,43	1		STK
-	<b>ZMVB90.60.600</b>	60	600			1,6	1		STK

### Te bevestigen met:



Zelfborgende  
moer en bout  
VM



Zelfborgende  
moer en  
kraagbout  
VMK

Minimum aantal bouten en moeren: 8 stuks.