


VS


Verloopstuk



Te bevestigen met:



Zelfborgende
moer en bout
VM



Zelfborgende
moer en
kraagbout
VMK

Op aanvraag: Hoogte 35 mm - 85 mm - 110 mm

Stand. Uitv.

Sendimir

Mat. Opt.

Mat. Opt. PE

Poedercoating

HD	Artikel	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Eenh.
-	VS60.025	50	25			0,080	1	X	STK
-	VS60.050	50	50			0,080	1	X	STK
-	VS60.075	50	75			0,090	1	X	STK
-	VS60.100	50	100			0,100	1	X	STK
-	VS60.125	50	125			0,100	1	X	STK
-	VS60.150	50	150			0,110	1	X	STK
-	VS60.200	50	200			0,120	1	X	STK
-	VS60.250	50	250			0,140	1	X	STK
-	VS60.300	50	300			0,180	1	X	STK
-	VS60.350	50	350			0,180	1	X	STK
-	VS60.400	50	400			0,210	1	X	STK
-	ZMVS60.025	50	25			0,088	1	X	STK
-	ZMVS60.050	50	50			0,088	1	X	STK
-	ZMVS60.075	50	75			0,099	1	X	STK
-	ZMVS60.100	50	100			0,11	1	X	STK
-	ZMVS60.125	50	125			0,11	1	X	STK
-	ZMVS60.150	50	150			0,121	1	X	STK
-	ZMVS60.200	50	200			0,132	1	X	STK
-	ZMVS60.250	50	250			0,154	1	X	STK
-	ZMVS60.300	50	300			0,198	1	X	STK
-	ZMVS60.350	50	350			0,198	1	X	STK
-	ZMVS60.400	50	400			0,231	1	X	STK

Minimum aantal bouten en moeren: 4 stuks.

