

KLM100B45

Horizontale bocht 45° voor KLM100



Te bevestigen met:



Zelfborgende
kraagbout (DIN
603)
RBK



Zelfborgende
flensmoer (DIN
6923)
RM

Radius: 600 mm

Stand. Uitv.

Sendzimir

Mat. Opt.

Mat. Opt. PE

Poedercoating

HD Artikel	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Eenh.
- KLM100B45.150	100	158			3,412	1		STK
- KLM100B45.200	100	208			3,628	1		STK
- KLM100B45.300	100	308			4,060	1		STK
- KLM100B45.400	100	408			4,493	1		STK
- KLM100B45.450	100	458			4,709	1		STK
- KLM100B45.500	100	508			5,283	1		STK
- KLM100B45.600	100	608			5,792	1		STK
- KLM100B45.750	100	758			6,556	1		STK
- KLM100B45.800	100	808			6,811	1		STK
- KLM100B45.900	100	908			7,320	1		STK
- KLM100B45.1000	100	1008			8,571	1		STK
- ZMKLM100B45.150	100	158			3,412	1		STK
- ZMKLM100B45.200	100	208			3,628	1		STK
- ZMKLM100B45.300	100	308			4,060	1		STK
- ZMKLM100B45.400	100	408			4,493	1		STK
- ZMKLM100B45.450	100	458			4,709	1		STK
- ZMKLM100B45.500	100	508			5,283	1		STK
- ZMKLM100B45.600	100	608			5,792	1		STK
- ZMKLM100B45.750	100	758			6,556	1		STK
- ZMKLM100B45.800	100	808			6,811	1		STK
- ZMKLM100B45.900	100	908			7,320	1		STK
- ZMKLM100B45.1000	100	1008			8,571	1		STK

Minimum aantal bouten en moeren: 8 stuks.