

KLM125B45

Horizontale bocht voor KLM125



Te bevestigen met:



Zelfborgende
kraagbout (DIN
603)
RBK



Zelfborgende
flensmoer (DIN
6923)
RM

Radius: 600 mm

Stand. Uitv.

Sendzimir

Mat. Opt.

Mat. Opt. PE

Poedercoating

HD	Artikel	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Eenh.
-	KLM125B45.150	125	158			4,084	1		STK
-	KLM125B45.200	125	208			4,312	1		STK
-	KLM125B45.300	125	308			4,767	1		STK
-	KLM125B45.400	125	408			5,223	1		STK
-	KLM125B45.450	125	458			5,451	1		STK
-	KLM125B45.500	125	508			6,035	1		STK
-	KLM125B45.600	125	608			6,567	1		STK
-	KLM125B45.750	125	758			7,366	1		STK
-	KLM125B45.800	125	808			7,632	1		STK
-	KLM125B45.900	125	908			8,165	1		STK
-	KLM125B45.1000	125	1008			9,438	1		STK
-	ZMKLM125B45.150	125	158			4,084	1		STK
-	ZMKLM125B45.200	125	208			4,312	1		STK
-	ZMKLM125B45.300	125	308			4,767	1		STK
-	ZMKLM125B45.400	125	408			5,223	1		STK
-	ZMKLM125B45.450	125	458			5,451	1		STK
-	ZMKLM125B45.500	125	508			6,035	1		STK
-	ZMKLM125B45.600	125	608			6,567	1		STK
-	ZMKLM125B45.750	125	758			7,366	1		STK
-	ZMKLM125B45.800	125	808			7,632	1		STK
-	ZMKLM125B45.900	125	908			8,165	1		STK
-	ZMKLM125B45.1000	125	1008			9,438	1		STK

Minimum aantal bouten en moeren: 8 stuks.